

## ■ 90°angle

**General attributes**

Additional features	Drag chain compatible
Approvals / Conformity	cULus LISTED
Cable jacket color	black
Enclosure Type per IEC 60529	IP68
Function indicator (PIN 4)	No
Power indicator	No

**Electrical attributes**

Operating voltage UB max. AC [V]	250.0 V
Operating voltage UB max. DC [V]	250.0 V
Rated current (40°C)	4.0 A
Switching function	Normally open (NO)
Switching output	No

**Mechanical attributes**

Acceleration max. (drag chain)	5 m/s <sup>2</sup>
Ambient temp. max. (fixed)	90 °C (UL 80 °C)
Ambient temp. max. (moving)	90 °C (UL 80 °C)
Ambient temp. max.(drag chain)	60 °C
Ambient temp. min. (fixed)	-50 °C
Ambient temp. min. (moving)	-25 °C
Ambient temp. min.(drag chain)	-25 °C
Bending cycles	> 5 Mio.
Bending radius fixed cable	min. 5 x D
Bending radius tensioned cable	min. 10 x D

Cable diameter D	4.3 +/- 0.20 mm
Cable jacket material	PUR
Cable length L [m]	2.00 m
Conductor cross-section	0.34 mm <sup>2</sup>
Connector configuration	90°angle
Connector type	M12x1
Contact material	CuZn
Cover nut material	GD-Zn
Drag chain compatible	Yes
Grip material	PUR
Number of conductors	3
Number of female/male pins	3
Permiss.horizon. traverse dist	at 5 m/sec <sup>2</sup> 5 m
Permiss.vert. traverse dist	at 5 m/sec <sup>2</sup> 5 m
System	molded
Tightening torque pigtail	0.6 Nm
Traverse speed max(drag chain)	at 5 m horiz. travel 200 m/min



**Additional text**

Enclosure type accord. to IEC 60529, when threaded together with the appropriate counterpart.  
 Raw Cable Approval UL+CSA, UL-AWM Style 21198 or 20549  
 Flame resistant per IEC 332-2  
 Silicone free  
 Halogen-free per DIN VDE 0472 Part 815

Connector/cable

**BCC M423-0000-2A-001-PX0334-020**

**Order code: BCC02ZY**



PIN 1: brown  
PIN 3: blue  
PIN 4: black