

### Display/Operation

|                 |    |
|-----------------|----|
| Power indicator | no |
|-----------------|----|

### Electrical connection

|                           |                   |
|---------------------------|-------------------|
| Cable diameter D          | 4...6 mm          |
| Connector 01, orientation | angled            |
| Number of pins            | 5                 |
| System                    | Can be fabricated |

### Electrical data

|                         |                   |
|-------------------------|-------------------|
| Operating voltage $U_b$ | 125 VDC / 125 VAC |
| Rated current (40 °C)   | 4.0 A             |

### Environmental conditions

|                     |             |
|---------------------|-------------|
| Ambient temperature | -40...85 °C |
|---------------------|-------------|

Protection type IEC 60529

IP67

### Material

|                          |               |
|--------------------------|---------------|
| Material contact carrier | PA            |
| Material contacts        | Brass         |
| Material cover nut       | Die-cast zinc |
| Material grip            | PA            |


### Mechanical data

|                           |                             |
|---------------------------|-----------------------------|
| Connection cross-section  | 0.14...0.75 mm <sup>2</sup> |
| Tightening torque pigtail | 0.6 Nm                      |
| Type of wire mounting     | Screw terminals             |

### Remarks

Enclosure rating per IEC 60529, only in screwed state with the associated mating piece.

### Connector view



PIN 1-5 usable