

- Female M8
- Male M8
- straight / straight



**General attributes**

Additional features	Drag chain compatible
Approvals / Conformity	cULus LISTED
Cable jacket color	yellow
Enclosure Type per IEC 60529	IP67 / IP67
Function indicator	No
Function indicator (PIN 2)	No
Function indicator (PIN 4)	No
Power indicator	No

**Electrical attributes**

Operating voltage UB max. AC [V]	30.0 V
Operating voltage UB max. DC [V]	30.0 V
Rated current (40°C)	4.0 A
Switching function	Complementary (NO/NC)
Switching output	No

**Mechanical attributes**

Ambient temp. max. (fixed)	105 °C
Ambient temp. max. (moving)	105 °C
Ambient temp. min. (fixed)	-50 °C
Ambient temp. min. (moving)	-40 °C
Bending cycles	> 10 Mio.
Bending radius fixed cable	min. 5 x D
Bending radius tensioned cable	min. 10 x D

Cable diameter D	5.3 +/- 0.13 mm
Cable jacket material	TPE
Cable length L [m]	5.00 m
Conductor cross-section	22 AWG
Connector configuration	straight / straight
Connector type	M08x1
Connector type (Header I)	Female M8
Connector type (Header II)	Male M8
Contact material	CuZn / CuZn
Cover nut material	GD-Zn / GD-Zn
Drag chain compatible	Yes
Grip material	polyether TPU
Number of conductors	4
Number of female/male pins	4 / 4
System	molded / molded
Tightening torque pigtail	0.4 Nm / 0.4 Nm



**Additional text**

Cable Conductors according to UL-20327  
 E54661 RU AWM STYLE 20327 105C 300V 22 AWG/3 LL54185 CSA AWM I/II A/B105C 300V FT1  
 Raw cable: E101876 22AWG/4 (UL) PLTC 105C or AWM 20327 105C 300V  
 Flame-Resistance FT1/VW-1  
 Flame-Retardant


Connector/cable

**BCC M314-M314-30-304-EX44T2-050**

**Order code: BCC0AAN**



II



I