

Display/Operation

Buzzer function	no
Function indicator	Chaser Level indicator Stack light
IO-Link communication indicator	LED green
Module supply indicator	LED green

Electrical connection

Contact, surface protection	nickel plated 2 µm/gold plated 0.4 µm
-----------------------------	--

Electrical data

Cycle time min.	5 ms
IO-Link function	Device
Operating voltage U_b	18...30.2 VDC
Rated operating voltage U_e DC	24 V
Segments, number max.	5

Environmental conditions

Ambient temperature	-5...50 °C
Protection type IEC 60529	IP65
Storage temperature	-25...50 °C

General data

Approval/Conformity	CE
Dimmable	yes
Life expectancy min.	50000 h

Predefined colors

yellow
white
green
blue
red

Scope of delivery

Lock washer
Rubber foot
Short guide
M4x6 screw
Hex nut M18x1

Material

Colors, number	7
Housing material	PC, Transparent
Housing shield	yes
Surface protection	zinc plated Cu8a Ni10s Cr

Mechanical data

Application weight	500.00 g
Dimension	60 x 60 x 310 mm
Fastening detail	1-hole screw mount
Frame type	2.V
Grounding cable attachment	M4


Output/Interface

Error signal	≤ 3x120+40 mA
IO-Link version	1.1
Process data cycle min.	5 ms
Process data in	0
Process data out	3 bytes

Remarks

Mounting instructions	See short guide
-----------------------	-----------------

Connector view



IO-Link PIN 1: +24V PIN 2: n.c. PIN 3: GND PIN 4:
C/Q, IO-Link DC-Channel