

## Display/Operation

Buzzer function	yes
Function indicator	Chaser Level indicator Stack light
IO-Link communication indicator	LED green
Module supply indicator	LED green

## Predefined colors

configurable  
 orange  
 yellow  
 white  
 green  
 blue  
 red

## Scope of delivery

Lock washer  
 Rubber foot  
 Short guide  
 M4x6 screw  
 Hex nut M18x1

## Electrical connection

Contact, surface protection	nickel plated 2 µm/gold plated 0.4 µm
-----------------------------	--

## Material

Colors, number	7
Gasket, material	FKM 75
Housing material	PC, Transparent
Housing shield	yes
Surface protection	Cu 15 µ Ni 15 µ

## Electrical data

Cycle time min.	7.2 ms
IO-Link function	Device
Operating voltage $U_b$	18...30.2 VDC
Rated operating voltage $U_e$ DC	24 V
Segments, number max.	3
Sound frequency	2800 ± 500 Hz

## Mechanical data

Application weight	470.00 g
Dimension	60 x 60 x 235 mm
Fastening detail	1-hole screw mount
Frame type	2.V
Grounding cable attachment	M4

## Environmental conditions

Ambient temperature	-5...50 °C
Protection type IEC 60529	IP30
Storage temperature	-25...50 °C
Volume max.	95 dB/m

## Output/Interface

Error signal	255 mA at 24V
IO-Link version	1.1
Process data cycle min.	7.2 ms
Process data in	1 byte
Process data out	8 bytes

## General data

Approval/Conformity	CE
Dimmable	yes
Life expectancy min.	50000 h


Mounting instructions

See short guide

Remarks

---

## Connector view



IO-Link PIN 1: +24V PIN 2: n.c. PIN 3: GND PIN 4:  
C/Q, IO-Link DC-Channel